

SPECIFICATION OF FUEL OIL 3,5%

| Property | Result | METHOD |
|--------------------------|---------------|---------------|
| Density at 15 0C | 0,9950 | ASTM D 1298 |
| Viscosity 50 C | 40 MAX | ASTM D 445 |
| Flash Point | 100 MIN | ASTM D 92 |
| Pour Point | 21 MAX | ASTM D 97 |
| Sulphur (S) | 3,5 MAX | ASTM D 1552 |
| Water | 0,30 | ASTM D 95 |
| Sediment | 0,03 | ASTM D 4870 |
| Ash | 0,10 MAX | ASTM D 482 |
| Vanadium (V) | 150 MAX | ASTM D 5863 |
| Sodium (NA) | 40 MAX | ASTM D 5863 |
| Asphaltene | 8 MAX | ASTM D 6560 |
| Al+Si | 84 | ASTM D 5863 |
| Total Acid Number | 0,07 | ASTM D 5863 |
| Caloric Value | 9200 MIN | ASTM D 240 |
| Copper | < 1 | |
| Total Sediment Potential | 0,03 | ASTM D 4870 |
| H2S | <0,5 | ASTM D 5863 |
| Nickel | 50 MAX | ASTM D 5863 |
| | | |